

Phosphoric Acid 75%

Product Properties

COLOR: Colorless
ODOR: None
pH: NA
SPECIFIC GRAVITY: 1.575
FOAMING: No
HARD WATER TOLERANCE: Yes

Description

Phosphoric Acid 75% is designed for soak, spray, and CIP application. For removal of mineral soils on stainless steel equipment. This pure phosphoric acid is excellent for pH adjustment.

Features...Benefits

Concentrated Economical
Hard Water Tolerant..... Improved Performance
Non-Foaming..... Improved Results

Directions

Wear protective clothing and gloves before opening. To remove mineral soils, use as-is or add to water. Place stainless steel equipment in an appropriate container, and carefully add solution until the stains and deposits are immersed. This product works quickly, soaking for long periods of time is unnecessary. Never pour this product back into the container. To adjust pH, add a few drops at a time, as needed for a lower pH.

Safety Information

DANGER

Causes severe skin burns and eye damage.

Wear protective gloves and eye protection. Wash thoroughly after handling. Do not breathe mist.

IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water. Wash contaminated clothing before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contacts if present and easy to do. Continue rinsing.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

Immediately call a POISON CENTER or physician.

1100 Central Industrial Dr.
St. Louis, Missouri, 63110

toll free: 800 325 9218
main: 314 771 6600
fax: 314 771 6608

www.interconchemical.com



160310-7040
© INTERCON 2016

REFER TO PRODUCT LABEL AND SDS
FOR ADDITIONAL INFORMATION